

# 1460

## **Protector**

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- · Also available with EMS Organizer and Dividers
- Personalized nameplate service available
- $\bullet$  Top lid opens up to 180° for on-the-field anti-roll stability when open
- · Watertight, crushproof, and dustproof
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Comfortable rubber over-molded handles
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Stainless steel hardware and padlock protectors



#### **CONFIGURATIONS**



1460 Standard



**1460AALG**With Custom Foam for 9430 / 9435



1460NF No Foam



1460WF With Foam

## **DIMENSIONS**

Interior (L×W×D) 18.54 x 9.92" x 10.92 (47.1 x 25.2 x 27.7 cm) Exterior (L×W×D) 20.85 x 12.73" x 12.75 (53 x 32.3 x 32.4 cm)

 Lid Depth
 4.91" (12.5 cm)

 Bottom Depth
 6.01" (15.3 cm)

 Total Depth
 10.92" (27.7 cm)

 Int Volume
 1.16 ft³ (0.033 m³)

 Padlock Hole Diameter
 0.31" (0.8 cm)

## **MATERIALS**

Body Polypropylene Latch EXL

O-Ring Polymer
Pins Stainless Steel

**Foam** Polyurethane

Purge Body ABS

**Purge Vent** 3 Micron Hydrophobic Non-Woven

## **COLOURS**



#### WEIGHT

 Weight With Foam
 12.48 lbs (5.7 kg)

 Weight Empty
 8.75 lbs (4 kg)

 Buoyancy
 82.00 lbs (37.2 kg)

## **TEMPERATURE**

**Minimum Temperature** -40°F (-40 °C) **Maximum Temperature** 210°F (98.9 °C)

#### **CERTIFICATIONS**

IP67

## **OTHER**

**Military** yes

## **ACCESSORIES**



**1461** 6 pc. Replacement Foam Set



**1463** Replacement O-ring



**1507** Quick Mounts - set of 4



1506TSA TSA Lock



**1500D** Desiccant Silica Gel

### Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 <u>sales@pelican.com</u> • <u>www.pelican.com</u>

Document created on 04-23-24