

1600

Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- Watertight, crushproof, and dustproof
- 2 level Pick N Pluck[™] with convoluted lid foam
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Stainless steel hardware and padlock protectors



CONFIGURATIONS



1600 Standard



1604 With Padded Dividers



1600NF No Foam



1600TPWith TrekPak Divider System



1600WF With Foam

DIMENSIONS

Interior (L×W×D) 21.51 x 16.54" x 7.99 (54.6 x 42 x 20.3 cm) Exterior (L×W×D) 24.39 x 19.36" x 8.79 (62 x 49.2 x 22.3 cm)

 Lid Depth
 1.75" (4.4 cm)

 Bottom Depth
 6.12" (15.5 cm)

 Total Depth
 7.87" (20 cm)

 Int Volume
 1.65 ft³ (0.047 m³)

 Padlock Hole Diameter
 0.31" (0.8 cm)

MATERIALS

Body Polypropylene

Latch ABS
O-Ring Polymer
Pins Stainless Steel
Foam 1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

COLOURS





OD Green

WEIGHT

 Weight With Foam
 14.11 lbs (6.4 kg)

 Weight Empty
 13.00 lbs (5.9 kg)

 Buoyancy
 117.00 lbs (53.1 kg)

 Master Pack Weight
 34.75 lbs (15.8 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 210°F (98.9 °C)

CERTIFICATIONS

IP67 MIL C-4150J Def Stan 81-41 ATA 300

OTHER

Master Pack2NameplateyesMilitaryyes

ACCESSORIES



Document created on 09-25-24