



1640

Protector

Transport Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- **4 strong polyurethane wheels with stainless steel bearings**
- **Watertight, crushproof, and dustproof**
- 3 level Pick N Pluck™ with convoluted lid foam
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Easy open double-throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Retractable extension trolley handle
- Stainless steel padlock protectors



CONFIGURATIONS



1640
Standard



1644
With Padded Dividers



1640NF
No Foam



1640WF
With Foam

DIMENSIONS

Interior (LxWxD)	23.70 x 24.00" x 13.90 (60.2 x 61 x 35.3 cm)
Exterior (LxWxD)	27.20 x 27.50" x 16.30 (69.1 x 69.9 x 41.4 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	11.90" (30.2 cm)
Total Depth	13.9" (35.3 cm)
Int Volume	4.58 ft ³ (0.13 m ³)
Padlock Hole Diameter	0.31" (0.8 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel

Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLOURS

 Black	 Desert Tan
---	--

WEIGHT

Weight With Foam	38.00 lbs (17.2 kg)
Weight Empty	34.00 lbs (15.4 kg)
Buoyancy	365.00 lbs (165.6 kg)
Master Pack Weight	50.00 lbs (22.7 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	210°F (98.9 °C)

CERTIFICATIONS

IP67
Def Stan 81-41

OTHER

Wheels	4
Extendable Handle	yes
Master Pack	1
Nameplate	yes
Reduced Area	yes

ACCESSORIES



0373
Replacement O-ring



0379
Lid Organizer



1641
5 pc. Replacement Foam Set



1642
Pick N Pluck™ Sections Only
(set of 3)



1507
Quick Mounts - set of 4



1506TSA
TSA Lock



1500D
Desiccant Silica Gel

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 09-20-24