



## 2410PL StealthLite™

Same features as the StealthLite™ 2410 LED Flashlight, but outfitted with a lens ring that emits a bright glow in the dark. The new generation photoluminescent material in the plastic absorbs the energy from any light source - fluorescent lights, the sun, or even the flashlight's own beam. No more fumbling in the dark for your flashlight. It is powered by 4 AA alkaline cells (included), submersible, and has an ELX body which resists chemicals, corrosion, and extreme temperatures.

- As bright as a Xenon light with the battery life of an LED
- Built Pelican tough
- Glow-in-the-dark shroud
- Super bright LED beam
- Unconditional Lifetime Guarantee of Excellence
- **NOW WITH NEW UPGRADED SPECS**
- Waterproof




### DIMENSIONS

<b>Length</b>	7.00" (17.8 cm)
---------------	-----------------

### MATERIALS

<b>Body</b>	EXL
<b>O-Ring</b>	Ethylene Propylene
<b>Lens</b>	Polycarbonate (PC)
<b>Shroud</b>	Photo luminescent Polycarbonate (PC)
<b>Contact Spring Retainer</b>	Stainless Steel / Phosphore Bronze

### COLOURS

 High Visibility Yellow
--

### LIGHT SPECS

<b>Lamp Type</b>	LED
------------------	-----

### POWER

<b>Battery Size</b>	AA
<b>Battery Type</b>	Alkaline
<b>Battery Quantity</b>	4
<b>Batteries Included</b>	yes
<b>Volts</b>	6.0v

### WEIGHT

<b>Weight With Batteries</b>	7.3 oz (207 gr)
<b>Weight Without Batteries</b>	3.7 oz (105 gr)
<b>Packaged Weight</b>	8.4 oz (238 gr)

SWITCH

**Switch Type**  
**Light Modes**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
One-handed Safety Switch  
On / Off

**Pelican**

[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)






Document created on 04-26-24

CERTIFICATIONS

- Class I, Division 1
- Class II, Division 1
- Class III, Division 1
- IECEX ia

OTHER

Submersible	yes
Minimum Pack	6
Package Code	C

FL1 STANDARD	HIGH
	183 LUMENS
	5h 45mins
	184m
	8480cd
	IPX7

ACCESSORIES