



3310CC

When you can't see the difference between one color cable from another, the job may be compromised. Now you can trust our select flashlights with new Correct Color technology to stop the guess work.

Common LED lights can produce an intense beam and lower CRI (Color Rendering Index), making it difficult to distinguish between different color cables and overpower your work area with blinding bright light. Our new Correct Color flashlights are engineered with a higher CRI(90+ Color Rendering Index) allowing you to see color more accurately in your work environment. And with a low temperature beam (similar to incandescent flashlights) you get the benefits of our Correct Color technology that doesn't outshine the details.

- 3 AA Batteries (Included)
- 2 Modes: High / Low
- Up to 169m Beam Distance
- Up to 283 Lumens
- Learn more about Correct Color Lights



DIMENSIONS

| | |
|---------------|-----------------|
| Length | 6.14" (15.6 cm) |
|---------------|-----------------|

MATERIALS

| | |
|---------------|--------------------------------------|
| Body | Photo luminescent Polycarbonate (PC) |
| O-Ring | EPDM |
| Lens | Polycarbonate (PC) |

COLOURS

■ Photoluminescent

LIGHT SPECS

| | |
|------------------|-----|
| Lamp Type | LED |
|------------------|-----|

POWER

| | |
|---------------------------|----------|
| Battery Size | AA |
| Battery Type | Alkaline |
| Battery Quantity | 3 |
| Batteries Included | yes |
| Volts | 4.5v |

WEIGHT

| | |
|---------------------------------|-----------------|
| Weight With Batteries | 6.2 oz (176 gr) |
| Weight Without Batteries | 3.7 oz (105 gr) |

SWITCH






Switch Type
Light Modes

Push Button
High / Low / Flashing

OTHER

Minimum Pack
Package Code

1
C

| FL1 STANDARD | HIGH | LOW |
|---|---------------|--------------|
|  | 283 LUMENS | 31 LUMENS |
|  | 8h 0mins | 175h 0mins |
|  | 169m | 50m |
|  | 7150cd | 625cd |
|  | IPX8 (1m) | |

ACCESSORIES



2469P
Replacement Battery

