

1400

Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- Watertight, crushproof, and dustproof
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- · Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Pick N Pluck™ with convoluted lid foam
- · Stainless steel hardware
- Stainless steel padlock protectors



CONFIGURATIONS







1400NF No Foam



1400WF With Foam

DIMENSIONS

Interior (L×W×D) 11.81 x 8.87" x 5.18 (30 x 22.5 x 13.2 cm) Exterior (L×W×D) 13.37 x 11.62" x 6.00 (34 x 29.5 x 15.2 cm)

 Lid Depth
 1.18" (3 cm)

 Bottom Depth
 4.00" (10.2 cm)

 Total Depth
 5.18" (13.2 cm)

 Int Volume
 0.31 ft³ (0.009 m³)

 Padlock Hole Diameter
 0.31" (0.8 cm)

MATERIALS

Body Polypropylene

LatchABSO-RingPolymerPinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

COLOURS







OD Green

WEIGHT

 Weight With Foam
 4.41 lbs (2 kg)

 Weight Empty
 3.97 lbs (1.8 kg)

 Buoyancy
 20.06 lbs (9.1 kg)

 Master Pack Weight
 22.60 lbs (10.3 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 210°F (98.9 °C)

CERTIFICATIONS

IP67 MIL C-4150J Def Stan 81-41 ATA 300

OTHER

Master Pack4NameplateyesMilitaryyes

ACCESSORIES



1401 3 pc. Replacement Foam Set



1403 Replacement O-ring



1400PFSpecial Application Panel Frame



1400TPKIT TrekPak Case Divider Kit



1507 Quick Mounts - set of 4



1506TSA TSA Lock



1500D Desiccant Silica Gel



1500CICorrosion Intercept Kit

Pelican

Document created on 04-19-24