

1520 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican[™] Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- Watertight, crushproof, and dustproof

Automatic pressure equalization valve - balances interior pressure, keeps water out

- Comfortable rubber over-molded handle
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Pick N Pluck[™] with convoluted lid foam
- Stainless steel hardware and padlock protectors



CONFIGURATIONS



1520 Standard



1524 With Padded Dividers



1526 With Convertible Travel Bag



1520NF No Foam



1520WF With Foam

DIMENSIONS

Interior (L×W×D)	18.06 x 12.89" x 6.72 (45.9 x 32.7 x 17.1 cm)
Exterior (L×W×D)	19.78 x 15.77" x 7.41 (50.2 x 40.1 x 18.8 cm)
Lid Depth	1.79" (4.5 cm)
Bottom Depth	4.93" (12.5 cm)
Total Depth	6.72" (17.1 cm)
Int Volume	0.91 ft ³ (0.026 m ³)
Padlock Hole Diameter	0.31" (0.8 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLOURS



WEIGHT

Weight With Foam	9.35 lbs (4.2 kg)
Wainht Franks	0.20 lbs (2.0 lss)
Weight Empty	8.29 lbs (3.8 kg)
Buoyancy	63.00 lbs (28.6 kg)
Master Pack Weight	23.30 lbs (10.6 kg)
5	. 5,

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)	
Maximum Temperature	210°F (98.9 °C)	

CERTIFICATIONS

IP67 MIL C-4150J Def Stan 81-41

OTHER

Master Pack	2		
Nameplate	yes		
Military	yes		

ACCESSORIES





1508 Photographer's Lid Organizer

1509 Lid Organizer



1521 3 pc. Replacement Foam Set



1506TSA TSA Lock



1523 Replacement O-ring



1500D Desiccant Silica Gel



1525 Padded Divider Set



1520PF Special Application Panel Frame



1520TPKIT TrekPak Case Divider Kit



1507 Quick Mounts - set of 4



1500CI Corrosion Intercept Kit

 Pelican

 23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

 sales@pelican.com
 • www.pelican.com

Document created on 04-24-24