



3315CC

When you can't see the difference between one color cable from another, the job may be compromised. Now you can trust our select flashlights with new Correct Color technology to stop the guess work.

Common LED lights can produce an intense beam and lower CRI (Color Rendering Index), making it difficult to distinguish between different color cables and overpower your work area with blinding bright light. Our new Correct Color flashlights are engineered with a higher CRI(90+ Color Rendering Index) allowing you to see color more accurately in your work environment. And with a low temperature beam (similar to incandescent flashlights) you get the benefits of our Correct Color technology that doesn't outshine the details.

- 3 AA Batteries (Included)
- Up to 110m Beam Distance
- Up to 130 Lumens
- Learn more about Correct Color Lights




DIMENSIONS

| | |
|---------------|-----------------|
| Length | 6.14" (15.6 cm) |
|---------------|-----------------|

MATERIALS

| | |
|---------------|--------------------|
| Body | High Impact ABS |
| O-Ring | EPDM |
| Lens | Polycarbonate (PC) |

COLOURS

| |
|--|
|  High Visibility Yellow |
|--|

LIGHT SPECS

| | |
|------------------|-----|
| Lamp Type | LED |
|------------------|-----|

POWER

| | |
|---------------------------|----------|
| Battery Size | AA |
| Battery Type | Alkaline |
| Battery Quantity | 3 |
| Batteries Included | yes |
| Volts | 4.5v |

WEIGHT

| | |
|---------------------------------|-----------------|
| Weight With Batteries | 6.2 oz (176 gr) |
| Weight Without Batteries | 3.7 oz (105 gr) |

SWITCH

| | |
|--------------------|-------------|
| Switch Type | Push Button |
|--------------------|-------------|

Light Modes

On / Off

CERTIFICATIONS

Class I, Division 1






IECEX ia

Class II, Division 1

Class III, Division 1

OTHER

Minimum Pack 1
Package Code C

| FL1 STANDARD | HIGH |
|---|---------------|
|  | 130 LUMENS |
|  | 16h 30mins |
|  | 110m |
|  | 3042cd |
|  | IP67 |

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 09-21-24