

# 1200

## Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

#### · Watertight, crushproof, and dustproof

- Automatic pressure equalization valve balances interior pressure, keeps water out
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Pick N Pluck™ with convoluted lid foam
- · Stainless steel hardware



#### **DIMENSIONS**

 Interior (L×W×D)
 9.31 x 7.13" x 4.12 (23.6 x 18.1 x 10.5 cm)

 Exterior (L×W×D)
 10.67 x 9.75" x 4.86 (27.1 x 24.8 x 12.3 cm)

 Lid Depth
 1.18" (3 cm)

 Bottom Depth
 2.93" (7.4 cm)

 Total Depth
 4.11" (10.4 cm)

 Int Volume
 0.16 ft³ (0.005 m³)

#### **MATERIALS**

**Body** Polypropylene

LatchABSO-RingPolymerPinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

**Purge Vent** 3 Micron Hydrophobic Non-Woven

## **COLORS**

Black Desert Tan Orange OD Green
Silver Yellow

#### WEIGHT

 Weight With Foam
 2.87 lbs (1.3 kg)

 Weight Empty
 2.65 lbs (1.2 kg)

 Buoyancy
 12.02 lbs (5.5 kg)

 Master Pack Weight
 25.00 lbs (11.3 kg)

# **TEMPERATURE**

**Minimum Temperature** -40°F (-40 °C) **Maximum Temperature** 210°F (98.9 °C)

## **CERTIFICATIONS**

IP67


Def Stan 81-41

## **OTHER**

Master Pack6Militaryyes

# **ACCESSORIES**







**1203** Replacement O-ring



**1200PF**Special Application Panel
Frame



**1200TPKIT** TrekPak Case Divider Kit



**1120TPDIV** Extra TrekPak Dividers



**1507** Quick Mounts - set of 4



**1506TSA** TSA Lock



**1500D** Desiccant Silica Gel

#### Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 <u>sales@pelican.com</u> • <u>www.pelican.com</u>

Document created on 04-26-24