



# 1430

## Protector

Top Loader Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **Unique top loading design**
- 3 level Pick N Pluck™ with convoluted lid foam
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Stainless steel hardware and padlock protectors
- Optional shoulder strap available



## DIMENSIONS

|                              |   |
|------------------------------|---|
| <b>Interior (L×W×D)</b>      | 13.56 x 5.76" x 11.70 (34.4 x 14.6 x 29.7 cm) |
| <b>Exterior (L×W×D)</b>      | 16.40 x 8.71" x 13.15 (41.7 x 22.1 x 33.4 cm) |
| <b>Lid Depth</b>             | 2.00" (5.1 cm)                                |
| <b>Bottom Depth</b>          | 9.70" (24.6 cm)                               |
| <b>Total Depth</b>           | 11.7" (29.7 cm)                               |
| <b>Int Volume</b>            | 0.53 ft³ (0.015 m³)                           |
| <b>Padlock Hole Diameter</b> | 0.31" (0.8 cm)                                |

## MATERIALS

|                   |                                |
|-------------------|--------------------------------|
| <b>Body</b>       | Polypropylene                  |
| <b>Latch</b>      | ABS                            |
| <b>O-Ring</b>     | Polymer                        |
| <b>Pins</b>       | Stainless Steel                |
| <b>Foam</b>       | 1.3 lb Polyurethane            |
| <b>Purge Body</b> | ABS                            |
| <b>Purge Vent</b> | 3 Micron Hydrophobic Non-Woven |

## COLORS

■ Black

## WEIGHT

|                           |                     |
|---------------------------|---------------------|
| <b>Weight With Foam</b>   | 6.50 lbs (2.9 kg)   |
| <b>Weight Empty</b>       | 5.60 lbs (2.5 kg)   |
| <b>Buoyancy</b>           | 59.00 lbs (26.8 kg) |
| <b>Master Pack Weight</b> | 8.09 lbs (3.7 kg)   |

TEMPERATURE

|                            |                 |
|----------------------------|-----------------|
| <b>Minimum Temperature</b> | -40°F (-40 °C)  |
| <b>Maximum Temperature</b> | 210°F (98.9 °C) |





CERTIFICATIONS

|                       |  |
|-----------------------|--|
| <b>IP67</b>           |  |
| <b>Def Stan 81-41</b> |  |

OTHER

|                    |     |
|--------------------|-----|
| <b>Master Pack</b> | 1   |
| <b>Nameplate</b>   | yes |
| <b>Military</b>    | yes |

ACCESSORIES

|   |   |   |  |   |
|---|---|---|--|---|
|    |    |    |    |    |
| <b>1431</b><br>5 pc. Replacement Foam Set   | <b>1432</b><br>Strap Kit  | <b>1433</b><br>Replacement O-ring   | <b>1435</b><br>Padded Divider Set  | <b>1436</b><br>Office Divider Kit   |
|  |  |  |  |  |
| <b>1438</b><br>Boat Bracket Kit   | <b>1439</b><br>Lid Organizer  | <b>1430PF</b><br>Special Application Panel Frame                                    | <b>PL2</b><br>Padlock (2 pack)   | <b>1506TSA</b><br>TSA Lock  |
|  |   |   |  |   |
| <b>1500D</b><br>Desiccant Silica Gel  |   |   |  |   |