



1550 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- **Watertight, crushproof, and dustproof**
- 2 level Pick N Pluck™ with convoluted lid foam
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Stainless steel hardware and padlock protectors



DIMENSIONS

| | |
|------------------------------|-----------------------------------------------|
| Interior (L×W×D) | 18.63 x 14.18" x 7.72 (47.3 x 36 x 19.6 cm) |
| Exterior (L×W×D) | 20.66 x 17.20" x 8.40 (52.5 x 43.7 x 21.3 cm) |
| Lid Depth | 1.75" (4.4 cm) |
| Bottom Depth | 5.87" (14.9 cm) |
| Total Depth | 7.62" (19.4 cm) |
| Int Volume | 1.18 ft³ (0.033 m³) |
| Padlock Hole Diameter | 0.31" (0.8 cm) |

MATERIALS

| | |
|-------------------|--------------------------------|
| Body | Polypropylene |
| Latch | ABS |
| O-Ring | Polymer |
| Pins | Stainless Steel |
| Foam | 1.3 lb Polyurethane |
| Purge Body | ABS |
| Purge Vent | 3 Micron Hydrophobic Non-Woven |

COLORS

| | | | |
|-------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|
|  Black |  Orange |  Silver |  Yellow |
|-------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|

WEIGHT

| | |
|---------------------------|---------------------|
| Weight With Foam | 11.90 lbs (5.4 kg) |
| Weight Empty | 10.58 lbs (4.8 kg) |
| Buoyancy | 69.89 lbs (31.7 kg) |
| Master Pack Weight | 28.35 lbs (12.9 kg) |

TEMPERATURE

| | |
|----------------------------|-----------------|
| Minimum Temperature | -40°F (-40 °C) |
| Maximum Temperature | 210°F (98.9 °C) |

CERTIFICATIONS

| | |
|-----------------------|--|
| IP67 | |
| MIL C-4150J | |
| Def Stan 81-41 | |
| ATA 300 | |

OTHER

| | |
|--------------------|-----|
| Master Pack | 2 |
| Nameplate | yes |
| Military | yes |

ACCESSORIES

| | | | | |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
|  |  |  |  |  |
| 1551 4 pc. Replacement Foam Set | 1552 Pick N Pluck™ Sections Only (set of 2) | 1553 Replacement O-ring | 1555 Padded Divider Set | 1550PF Special Application Panel Frame |
|  |  |  |  |  |
| 1550TPKIT TrekPak Case Divider Kit | 1510TPDIV Extra TrekPak Dividers | 1507 Quick Mounts - set of 4 | 1506TSA TSA Lock | 1500D Desiccant Silica Gel |
|  | | | | |
| PL2 Padlock (2 pack) | | | | |