



1620 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- **Strong polyurethane wheels with stainless steel bearings**
- **Watertight, crushproof, and dustproof**
- 4 level Pick N Pluck™ with convoluted lid foam
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Easy open double-throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors



DIMENSIONS

| | |
|------------------------------|------------------------------------------------|
| Interior (L×W×D) | 21.48 x 16.42" x 12.54 (54.6 x 41.7 x 31.9 cm) |
| Exterior (L×W×D) | 24.76 x 19.57" x 13.90 (62.9 x 49.7 x 35.3 cm) |
| Lid Depth | 2.01" (5.1 cm) |
| Bottom Depth | 10.53" (26.7 cm) |
| Total Depth | 12.54" (31.9 cm) |
| Int Volume | 2.56 ft³ (0.072 m³) |
| Padlock Hole Diameter | 0.31" (0.8 cm) |

MATERIALS

| | |
|-------------------|--------------------------------|
| Body | Polypropylene |
| Latch | ABS |
| O-Ring | Polymer |
| Pins | Stainless Steel |
| Foam | 1.3 lb Polyurethane |
| Purge Body | ABS |
| Purge Vent | 3 Micron Hydrophobic Non-Woven |

COLORS

| | | |
|-------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|
|  Black |  Desert Tan |  OD Green |
|-------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|

WEIGHT

| | |
|---------------------------|---------------------|
| Weight With Foam | 24.62 lbs (11.2 kg) |
| Weight Empty | 21.20 lbs (9.6 kg) |
| Buoyancy | 149.91 lbs (68 kg) |
| Master Pack Weight | 26.90 lbs (12.2 kg) |

TEMPERATURE

| | |
|----------------------------|-----------------|
| Minimum Temperature | -40°F (-40 °C) |
| Maximum Temperature | 210°F (98.9 °C) |

CERTIFICATIONS

| |
|-----------------------|
| IP67 |
| MIL C-4150J |
| Def Stan 81-41 |

OTHER

| | |
|--------------------------|-----|
| Wheels | 2 |
| Extendable Handle | yes |
| Master Pack | 1 |
| Nameplate | yes |
| Military | yes |

ACCESSORIES

| | | | | |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
|  |  |  |  |  |
| 1609 Lid Organizer | 1621 6 pc. Replacement Foam Set | 1622 Pick N Pluck™ Sections Only (set of 4) | 1623 Replacement O-ring | 1625 Padded Divider Set |
|  |  |  |  | |
| 1507 Quick Mounts - set of 4 | 1506TSA TSA Lock | 1500D Desiccant Silica Gel | PL2 Padlock (2 pack) | |