



# 0450

## Protector

Mobile Tool Chest

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Auto pressure equalization valves
- Download the 0450 Mobile Tool Chest Brochure
- Graduated deflector ribs
- Heavy duty buttress hinges
- Hybrid double throw butterfly latches
- Optional drawers
- Secure stack design
- Stable, wide track mobility
- The tool chest also includes three unsealed pockets on the left side to store smaller items.
- Tools and foam shown not included.
- Trolley handle & wheel system
- Two way handles



## CONFIGURATIONS



**0450**  
Standard



**0450WD**  
With Drawers

## DIMENSIONS

<b>Interior (L×W×D)</b>	20.56 x 10.97" x 12.65 (52.2 x 27.9 x 32.1 cm)
<b>Exterior (L×W×D)</b>	23.95 x 14.75" x 17.95 (60.8 x 37.5 x 45.6 cm)
<b>Int Volume</b>	1.65 ft <sup>3</sup> (0.047 m <sup>3</sup> )

## MATERIALS

<b>Body</b>	Polypropylene
<b>Latch</b>	ABS
<b>O-Ring</b>	Polymer
<b>Pins</b>	Stainless Steel
<b>Purge Body</b>	ABS
<b>Purge Vent</b>	3 Micron Hydrophobic Non-Woven

COLORS

---

■ Black

WEIGHT

---

<b>Weight Empty</b>	32.00 lbs (14.5 kg)
<b>Weight With Drawers</b>	41.50 lbs (18.8 kg)
<b>Weight With Drawers and Tray</b>	43.50 lbs (19.7 kg)
<b>Master Pack Weight</b>	34.50 lbs (15.6 kg)

CERTIFICATIONS

---

**MIL-STD-810F**

OTHER

---

<b>Master Pack</b>	1
--------------------	---

ACCESSORIES

---



**1500CI**  
Corrosion Intercept Kit

---

**Pelican**  
23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 05-09-24*