



1730

Protector

Transport Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- **Watertight, crushproof, and dustproof**
- 5-piece foam set
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Easy open double-throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Optional Humidity gauge changes color above 40%
- Optional Manual Pressure Equalization Valve
- Stainless steel hardware and padlock protectors



CONFIGURATIONS



1730
Standard



1730NF
No Foam



1730WF
With Foam

DIMENSIONS

Interior (L×W×D)	34.00 x 24.00" x 12.50 (86.4 x 61 x 31.8 cm)
Exterior (L×W×D)	37.50 x 27.13" x 14.37 (95.3 x 68.9 x 36.5 cm)
Lid Depth	2.50" (6.4 cm)
Bottom Depth	10.00" (25.4 cm)
Total Depth	12.5" (31.8 cm)
Int Volume	5.9 ft³ (0.167 m³)
Padlock Hole Diameter	0.31" (0.8 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel

Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLORS

 Black	 Desert Tan	 OD Green
---	--	--

WEIGHT

Weight With Foam	38.00 lbs (17.2 kg)
Weight Empty	30.00 lbs (13.6 kg)
Buoyancy	416.00 lbs (188.7 kg)
Master Pack Weight	43.00 lbs (19.5 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	210°F (98.9 °C)

CERTIFICATIONS

IP67

OTHER

Wheels	2
Master Pack	1
Nameplate	yes

ACCESSORIES



1731
5 pc. Replacement Foam Set



1733
Replacement O-ring



1506TSA
TSA Lock



1500D
Desiccant Silica Gel



1500CI
Corrosion Intercept Kit

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 04-19-24