



## 1495CC2

### Protector

#### Laptop Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- Combination Lock Information
- **3 dial combination lock included**
- **Fits up to 17" laptops**
- **Watertight, crushproof, and dustproof**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Easy open double-throw latches
- Fold down over-molded handle
- Lid organizer and padded shoulder strap
- Stainless steel padlock protectors



#### DIMENSIONS

|                              |                                               |
|------------------------------|-----------------------------------------------|
| <b>Interior (L×W×D)</b>      | 18.87 x 13.12" x 3.81 (47.9 x 33.3 x 9.7 cm)  |
| <b>Exterior (L×W×D)</b>      | 21.62 x 17.25" x 4.87 (54.9 x 43.8 x 12.4 cm) |
| <b>Lid Depth</b>             | 1.12" (2.8 cm)                                |
| <b>Bottom Depth</b>          | 2.68" (6.8 cm)                                |
| <b>Total Depth</b>           | 3.8" (9.7 cm)                                 |
| <b>Int Volume</b>            | 0.55 ft³ (0.016 m³)                           |
| <b>Padlock Hole Diameter</b> | 5/16" (12.7 cm)                               |

#### MATERIALS

|                   |                                |
|-------------------|--------------------------------|
| <b>Body</b>       | Polypropylene                  |
| <b>Latch</b>      | ABS                            |
| <b>O-Ring</b>     | Polymer                        |
| <b>Pins</b>       | Stainless Steel                |
| <b>Foam</b>       | 1.3 lb Polyurethane            |
| <b>Purge Body</b> | ABS                            |
| <b>Purge Vent</b> | 3 Micron Hydrophobic Non-Woven |

#### COLORS

|                                                                                           |                                                                                                |
|-------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|
|  Black |  Desert Tan |
|-------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|

#### WEIGHT

|                           |                     |
|---------------------------|---------------------|
| <b>Weight With Foam</b>   | 8.99 lbs (4.1 kg)   |
| <b>Buoyancy</b>           | 45.15 lbs (20.5 kg) |
| <b>Master Pack Weight</b> | 26.00 lbs (11.8 kg) |

TEMPERATURE

|                            |                 |
|----------------------------|-----------------|
| <b>Minimum Temperature</b> | -40°F (-40 °C)  |
| <b>Maximum Temperature</b> | 210°F (98.9 °C) |

CERTIFICATIONS

|                       |  |
|-----------------------|--|
| <b>IP67</b>           |  |
| <b>Def Stan 81-41</b> |  |

OTHER

|                    |     |
|--------------------|-----|
| <b>Master Pack</b> | 2   |
| <b>Nameplate</b>   | yes |

ACCESSORIES

|                                                                                     |                                                                                     |                                                                                   |                                                                                    |                                                                                     |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|    |    |  |  |  |
| <b>1483</b><br>Replacement O-ring                                                   | <b>1495ALI</b><br>Attache/Computer Lid Insert                                       | <b>1495CBI</b><br>Computer Bottom Insert                                          | <b>1495HDF</b><br>4 lb. High Density Foam                                          | <b>1506TSA</b><br>TSA Lock                                                          |
|  |  |                                                                                   |                                                                                    |                                                                                     |
| <b>1500D</b><br>Desiccant Silica Gel                                                | <b>1500CI</b><br>Corrosion Intercept Kit                                            |                                                                                   |                                                                                    |                                                                                     |

**Pelican**  
23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

Document created on 04-16-24