



## 3315R-RA

### Right Angle Light

Ultra compact, special designed lithium rechargeable and safety certified right angle make the Pelican™ 3315R-RA one of the most versatile work lights available today. Its compact and right angle design is perfect for any hands free applications. The articulating head allows for the light to be used as a conventional handheld light in addition to having the ability to direct the light exactly where you need it. The 3315R-RA produces up to 132 lumens and provides up to 34 hours of continuous run time. 3 modes are provided, High / Low / Flashing. There is a full time battery level indicator built into the power switch so you'll always know when it's time to recharge.

- IPX7 Waterproof
- Full Time Battery Level Indication
- 3 modes High / Strobe / Low
- Safety Certified Class I, Division 1 / IECEx ia
- Lanyard (included)
- Special Lithium rechargeable battery provides 2,000 cycles (a 300% increase)
- Up to 132 Lumens
- Up to 34 hours, 15 minutes run time
- Articulating right angle adapter with clip (included)




### DIMENSIONS

<b>Length</b>	8.27" (21 cm)
---------------	---------------

### MATERIALS

<b>Body</b>	Anti-static Impact Modified PC/PBT
<b>O-Ring</b>	EPDM
<b>Lens</b>	Anti-static coated Polycarbonate (PC)
<b>Shroud</b>	Anti-static Impact Modified PC/PBT
<b>Clip</b>	Stainless Steel

### COLORS

 High Visibility Yellow
--

### LIGHT SPECS

<b>Lamp Type</b>	LED
------------------	-----

### POWER

<b>Battery Size</b>	18650
<b>Battery Type</b>	Lithium Iron Phosphate
<b>Battery Quantity</b>	1
<b>Batteries Included</b>	yes
<b>Rechargeable</b>	yes
<b>Charge Time</b>	10 hrs
<b>Battery Level Indicator</b>	RGB LED
<b>Volts</b>	3.2v

## WEIGHT

---

<b>Weight With Batteries</b>	6.2 oz (176 gr)
<b>Weight Without Batteries</b>	3.7 oz (105 gr)

## SWITCH

---

<b>Switch Type</b>	Push Button
<b>Light Modes</b>	High / Low / Flashing

## CERTIFICATIONS






---

**Class I, Division 1  
IECEX ia**

## OTHER

---

<b>Minimum Pack</b>	1
<b>Package Code</b>	C

<b>FL1 STANDARD</b>	<b>HIGH</b>	<b>LOW</b>
	132 LUMENS	15 LUMENS
	5h 0mins	34h 0mins
	108m	35m
	2931cd	308cd
	IP67	

## ACCESSORIES

---



**0780**  
Helmet Light Holder



**3317**  
Right Angle Adapter



**3318**  
Deck/Dash Charger Base Unit



**2467F**  
110V Transformer (USA)



**3319**  
Replacement Battery



**6061F**  
Direct Wiring Rig for Fast  
Charger



**3313**  
Nylon Holster



**8056F**  
12v Plug-in for Fast Charger

---

**Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 01-25-20*