



EX448

Trade Show Tower

Trusted for over 40 years by the US Military, Single Lid Cases offer 20% more protective material in the edges and corners, where it is needed most, ensuring that valuable equipment is kept safe from any unforeseen elements. Available in several sizes, these cases are completely customizable with a wide range of bolt-on options like document holders, casters, humidity indicators and much more.

- Military style butterfly stainless steel catch and strike latches
- Lockable - stainless steel cable catch with stainless steel cable
- Weather Resistant full EPMD rubber door gasket (durometer shore A53, (hardness))
- Rugged galvanized steel door hinges coated with zinc plating, clear trivalent chromate
- Large detent area for labeling on front and rear which prevents scraping (scrape proof)
- Stacking ribs enable stacking two high horizontally
- Pelican one year guarantee
- 15% to 20% thicker, naturally reinforced corners and edges for additional impact protection
- Sold exclusively by Silver State Case Company: 844-243-8500
- www.silverstatecase.com



DIMENSIONS

Interior (LxWxD)	97.94 x 44.88" x 50.26 (248.8 x 114 x 127.7 cm)
Exterior (LxWxD)	108.00 x 48.22" x 58.80 (274.3 x 122.5 x 149.4 cm)
Lid Depth	0.00" (0 cm)
Bottom Depth	0.00" (0 cm)
Total Depth	0" (0 cm)
Int Volume	127.85 ft ³ (3.62 m ³)

MATERIALS

Body	RotoMolded Polyethylene
Latch	Steel (Nickel-black Plated)
O-Ring	Silicone Sponge
Foam	No Foam, empty case standard Optional PE and PU, 1 and 2 lb. options filled and lined
Purge Body	Aluminum
PRV Valve	.5 PSI Standard, Light Lift .25 PSI
Handle	Heavy Duty Injection Molded Standard
Optional Handles	Stainless Steel Passivate and Stainless Steel Black
Hardware	Yellow Carbon Steel Standard
Optional Hardware	Black Carbon Steel, Stainless Steel Passivate and Stainless Steel Black

COLORS

■ Gray - 133 Fed Std
26270

WEIGHT

Weight	372.00 lbs (168.7 kg)
---------------	-----------------------

Buoyancy	0.00 lbs (0 kg)
Master Pack Weight	372.00 lbs (168.7 kg)

TEMPERATURE

Minimum Temperature	-20°F (-28.9 °C)
Maximum Temperature	140°F (60 °C)

OTHER

Military	yes
-----------------	-----

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 04-26-24