



## AL2414-0509AC/HL

Trusted for over 40 years by the US Military, Single Lid Cases offer 20% more protective material in the edges and corners, where it is needed most, ensuring that valuable equipment is kept safe from any unforeseen elements. Available in several sizes, these cases are completely customizable with a wide range of bolt-on options like document holders, casters, humidity indicators and much more.

- Refuerzos moldeados en forma de lengüeta para un sellado perfecto, resistente al agua y a los impactos
- Esquinas y bordes reforzados para una mayor protección frente a impactos
- Nervios y ondulaciones moldeados que permiten apilar las cajas de manera segura y a prueba de deslizamientos
- Piezas de metal integradas para una mayor protección
- Candados anticizalla que evitan el desprendimiento de la tapa tras un impacto y reducen la tensión sobre los pernos
- Inserciones de metal moldeadas patentadas para puntos de fijación de cierres y bisagras que fortalecen las paredes
- Estructura de una pieza moldeada en polietileno ligero y de gran resistencia frente a impactos



### DIMENSIONES

<b>INTERIOR</b>	24.62 x 14.57" x 14.52 (62.5 x 37 x 36.9 cm)
<b>EXTERIOR</b>	27.62 x 17.57" x 16.71 (70.2 x 44.6 x 42.4 cm)
<b>profundidad tapa</b>	9.34" (23.7 cm)
<b>profundidad base</b>	5.18" (13.2 cm)
<b>profundidad total</b>	14.52" (36.9 cm)
<b>volumen interior</b>	3.01 ft <sup>3</sup> (0.085 m <sup>3</sup> )

### MATERIALES

<b>cuerpo</b>	RotoMolded Polyethylene
<b>cierre</b>	Steel (Nickel-black Plated)
<b>anillo de sellado de neopreno</b>	Silicone Sponge
<b>pasadores</b>	Stainless Steel
<b>Pasadores (Alt)</b>	Aluminum
<b>cuerpo de compensación</b>	Aluminum

### COLORES

■ Gray - 133 Fed Std  
26270

### PESO

<b>peso</b>	23.60 lbs (10.7 kg)
<b>flotabilidad</b>	269.38 lbs (122.2 kg)
<b>Master Pack Weight</b>	25.60 lbs (11.6 kg)

## LA TEMPERATURA

---

**temperatura mínima** -20°F (-28.9 °C)  
**temperatura máxima** 140°F (60 °C)

## OTRAS

---

**Aplicaciones militares** sí

---

### **Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 10-18-19*