



## 2785

Torçe Frontali

At long last, a high performance / long run time safety certified headlamp! The Class I, Division 1 / IECEx certified 2785 provides a Main, Downcast, Flashing, and combination LED modes. The focused Main LED provides a great distance beam while the Downcast LED projects a dispersed beam set at a 45° downward angle. This "Downcast" beam offers a number of benefits including safer illuminated pathways, reading capability, as well as convenient face to face applications. Options are plentiful as each mode is provided in an easy to select high, medium or low setting. The rear mounted battery pack is equipped with a full time battery level indicator in addition to a rear facing red LED for added safety. With over 200 lumens of high intensity light output available, coupled with the ability to last up to 100 hours in the low setting, the 2785 will support virtually all your hands free lighting needs. All this in a product that carries intrinsically safe certifications.

- 4 pile alcaline AA (include)
- Testa rotante per il fascio di luce direzionale (70°)
- LED rosso a doppia modalità montato posteriormente
- Doppie fasci luminosi, inclusa la tecnologia dei LED che puntano verso il basso
- 3 livelli di luminosità
- Indicazione di livello di carica della batteria a tempo pieno
- Cinghie di gomma e di tessuto incluse



### DIMENSIONI

**lunghezza** 3.00" (7.6 cm)

### MATERIALI

**corpo** Polycarbonate (PC)  
**o-ring** Gasket  
**lente** Polycarbonate (PC)  
**copertura** Polycarbonate (PC)

### COLORI

■ Black      ■ High Visibility Yellow

### LIGHT SPECS

**tipo di lampada** LED  
**Lamp Secondary Type** LED

### POWER

**dimensioni batteria** AA  
**tipo batteria** Alkaline  
**quantità di batterie** 4  
**batterie incluse** sì  
**Indicatore di livello della batteria** 3 Blue LEDs  
**volt** 6.0v

## IL PESO






<b>peso con batterie</b>	8.8 oz (249 gr)
<b>peso senza batterie</b>	6.6 oz (187 gr)

## SWITCH

<b>tipo interruttore</b>	Rotary / Push Button
<b>modalità luminose</b>	High / Medium / Low / Downcast / Spot / Flashing

## CERTIFICAZIONI

**Class I, Division 1**  
**IECEX ia**

<b>FL1 STANDARD</b>	<b>MAIN HIGH</b>	<b>MAIN MED</b>	<b>MAIN LOW</b>
	215 LUMENS	106 LUMENS	22 LUMENS
	5h 0mins	13h 0mins	98h 0mins
	108m	76m	34m
	2911cd	1445cd	290cd
	IP54		

## ACCESSORI



**0783**  
Head Strap Retainers

---

**Pelican**  
23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 10-14-19*