

2010Z0 SabreLite™

The SabreLite [™] 2010Z0 LED is Peli's flagship LED torch. The rugged, light weight anti-static PC/PBT resin body is submersible to 1 meter for 30 mins (IPX7) and a twist on/off lens shroud eliminates accidental discharge. It is powered by 3 C alkaline cells. The SabreLite[™] 2010Z0 is the future of LEDs. Certified to ATEX Zone 20.



DIMENSIONS

| Length | 8.11" (20.6 cm) |
|-------------------------|------------------------------------|
| MATERIALS | |
| Body | Anti-static PC/PBT |
| O-Ring | Ethylene Propylene |
| Lens | Anti-static PMMA |
| Shroud | Anti-static Impact Modified PC/PBT |
| Clip | Anti-static Impact Modified PC/PBT |
| Contact Spring Retainer | Stainless Steel / Brass Nickel |
| | |
| | |

COLOURS

High Visibility Yellow

LIGHT SPECS

| Lamp Type | LED |
|-----------|-----|
| POWER | |

| С |
|----------|
| Alkaline |
| 3 |
| 4.5v |
| |

WEIGHT

| Weight With Batteries | 13.4 oz (380 gr) |
|-----------------------------|------------------|
| Weight Without Batteries | 5.4 oz (153 gr) |

SWITCH

| Switch Type | Twisting Lens Shroud |
|-------------|----------------------|
| Light Modes | On / Off |

CERTIFICATIONS

ATEX Zone 0

OTHER

| Submersible | | |
|--------------|--|--|
| Minimum Pack | | |
| Package Code | | |

yes 1 C

| FL1 STANDARD | HIGH |
|--------------|---------------|
| J'AZ | 129 LUMENS |
| | 22h 0mins |
| | 135m |
| | 4582cd |
| | IPX7 |

Peli c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 09-17-25