



1646

Air

Pelican understands that finding the right protection, with the perfect fit for your gear, is a priority. Pelican™ Air began with long protection and quickly grew to offer you deep protection. The time has come to combine those two in order to create Pelican's new Long/Deep Series. Gone are the days of dangerously forcing your equipment into the wrong size case or leaving it unprotected with no other options. With Pelican's Long/Deep series, we've created the missing link so that no matter the demands of your gear, Pelican has you covered.

- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Fold down over-molded handle
- Retractable extension trolley handle
- Stainless steel padlock protectors
- Business card holder
- Quiet rolling stainless-steel bearing wheels
- Press and Pull™ Latches
- Limited Lifetime Warranty
- Super-light proprietary HPX²™ Polymer - up to 40% lighter
- Waterproof O-ring seal
- Waterproof, crushproof, dustproof
- IP67 & MIL-SPEC certified
- Made in the USA



CONFIGURATIONS



1646
Standard



1646NF
No Foam



1646WF
With Foam

DIMENSIONS

Interior (L×W×D)	32.06 x 15.87" x 13.42 (81.4 x 40.3 x 34.1 cm)
Exterior (L×W×D)	35.29 x 19.00" x 15.08 (89.6 x 48.3 x 38.3 cm)
Lid Depth	1.98" (5 cm)
Bottom Depth	11.44" (29.1 cm)
Total Depth	13.42" (34.1 cm)
Int Volume	3.95 ft ³ (0.112 m ³)
Padlock Hole Diameter	0.31" (0.8 cm)

MATERIALS

Body	Proprietary Polypropylene Blend
Latch	ABS
O-Ring	EPDM

Purge Body	ABS
Purge Vent	Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven

COLORS

■ Black


WEIGHT

Weight With Foam	25.70 lbs (11.7 kg)
Weight Empty	20.50 lbs (9.3 kg)
Buoyancy	263.00 lbs (119.3 kg)

TEMPERATURE

Minimum Temperature	0°F (-17.8 °C)
Maximum Temperature	140°F (60 °C)

ACCESSORIES



1646AirFS
9 pc. Replacement Foam Set



1500CI
Corrosion Intercept Kit



AIRHANDL
EZ-Pull Multi-Stage Air Handle

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 08-01-25