

1720 Protector Long Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican[™] Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

• Strong polyurethane wheels with stainless steel bearings

- Watertight, crushproof, and dustproof
- 3-piece foam set
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Stainless steel hardware and padlock protectors
- 12 lid bosses for mounting of multiple 1500MP EZ-Click[™] MOLLE Panels
- Fold-down side handles on both ends additional carrying options
- New fold-down over-molded top and side handles
- *1500 EZ-Click $^{\scriptscriptstyle\rm TM}$ MOLLE Panels sold separately. Now available for purchase



CONFIGURATIONS



1720 Standard



1720WF With Foam



1720NF No Foam

DIMENSIONS

Interior (L×W×D)	41.80 x 13.58" x 5.33 (106.2 x 34.5 x 13.5 cm)
Exterior (L×W×D)	44.48 x 16.07" x 6.25 (113 x 40.8 x 15.9 cm)
Int Volume	1.75 ft³ (0.05 m³)
Padlock Hole Diameter	0.31" (0.8 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS

Purge Vent

COLORS



Desert Tan

OD Green

WEIGHT

Weight With Foam	23.10 lbs (10.5 kg)
Weight Empty	18.25 lbs (8.3 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	190°F (87.8 °C)

OTHER

Nameplate

yes

ACCESSORIES



1500MP EZ-Click[™] MOLLE Panel



1506TSA TSA Lock



1500D Desiccant Silica Gel



1723 Replacement O-ring



1721FS 3 pc. Replacement Foam Set



1720PRS RE-SET Kit



1111 88 0000



 Pelican

 23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

 sales@pelican.com
 • www.pelican.com

Document created on 09-15-25