

1965i

MityLite™

YOUR WORLDWIDE PASSPORT THROUGH HAZARDOUS LOCATIONS

While working in hazardous locations, remember a flashlight can be an ignition source. When you need the latest and brightest LED technology in a compact form factor, choose the new **MityLite** $^{\text{TM}}$ **1965 LED** from Pelican. Small enough to fit in your shirt pocket, yet bright enough to illuminate your work area.

Long lasting, energy efficient, bright LEDs, along with a compact package make the new **MityLite™** 1965 LED the safety approved light for the job.



DIMENSIONS

Length 5.48" (13.9 cm)

MATERIALS

Body EXL O-Ring EPDM

Lens Clear Polycarbonate (PC)

Shroud EXL Clip EXL

Contact Spring Retainer Phosphore Bronze

COLORS

High Visibility Yellow

LIGHT SPECS

Lamp Type LED

POWER

Battery SizeAAABattery TypeAlkalineBattery Quantity2Batteries IncludedyesVolts3.0v

WEIGHT

Weight With Batteries 1.9 oz (54 gr)
Weight Without
Batteries 1.1 oz (31 gr)

SWITCH

Switch Type Rotary

CERTIFICATIONS

IECEx ia Class I, Division 1 Class II, Division 1 Class III, Division 1

OTHER

Minimum Pack 12 Package Code C

FL1 STANDARD	HIGH
31/4	87 LUMENS
	2h 30mins
	41m
	429cd
	2m
T	IPX7