

# 2315

The hazard horizon is bright. With Class I, II, III – Division 1 and IECEx ia Safety Certification, 115 lumens and 75 meters of spot beam distance, the Pelican™ 2315 flashlight stretches light across dark, hazardous environments without being a source of ignition.

Engineered with an aluminum core and ABS overmolded plastic, these flashlights are built for rough handling and can survive hard drops. Plus, the sturdy clip attaches to a work vest for fast access and the tail switch activates raw LED power, even when using heavy-duty work gloves.

### Pelican™ 2315 - SEE THE LIGHT AT THE END OF THE TUNNEL

- Built Pelican tough
- 2 AA Batteries (included)
- Integrated Clip
- Full / Momentary Activation Tail Switch
- Class I, II, III Division 1 / IECEx ia Safety Certified
- IPX8 1m waterproof
- Helmet mount (included)



### **DIMENSIONS**

Length	6.22" (15.8 cm)
--------	-----------------

#### **MATERIALS**

Body	ABS
O-Ring	NBR
Lens	PC
Shroud	ABS
Clip	ABS

### **COLORS**

High Visibility Yellow

## LIGHT SPECS

Lamp	Туре		LED
------	------	--	-----

#### **POWER**

Battery Size	AA
Battery Type	Alkaline
<b>Battery Quantity</b>	2
<b>Batteries Included</b>	yes
Volts	3.0v

## WEIGHT

Weight With Batteries 4.6 oz (130 gr)
Weight Without
Batteries 2.8 oz (79 gr)

# **SWITCH**

Switch Type

Momentary Push Button

**Light Modes** High

**CERTIFICATIONS** 

Class I, Division 1 Class II, Division 1 Class III, Division 1 IECEx ia

FL1 STANDARD	HIGH
31/4	115 LUMENS
	6h 0mins
	75m
	1403cd
	IPX8 (1m)

### Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 <u>sales@pelican.com</u> • <u>www.pelican.com</u>

Document created on 10-31-25