



# 1495

## Protector

### Laptop Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- Combination Lock Information
- **3 dial combination lock included**
- **Fits up to 17" laptops**
- **Watertight, crushproof, and dustproof**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Easy open double-throw latches
- Fold down over-molded handle
- Lifetime Guarantee of Excellence
- Padded shoulder strap
- Pick N Pluck™ with convoluted lid foam
- Stainless steel padlock protectors



## CONFIGURATIONS



**1495**  
Standard



**1495NF**  
No Foam



**1495WF**  
With Foam

## DIMENSIONS


<b>Interior (L×W×D)</b>	18.87 x 13.12" x 3.81 (47.9 x 33.3 x 9.7 cm)
<b>Exterior (L×W×D)</b>	21.62 x 17.25" x 4.87 (54.9 x 43.8 x 12.4 cm)
<b>Lid Depth</b>	1.12" (2.8 cm)
<b>Bottom Depth</b>	2.68" (6.8 cm)
<b>Total Depth</b>	3.8" (9.7 cm)
<b>Int Volume</b>	0.55 ft³ (0.016 m³)
<b>Padlock Hole Diameter</b>	0.25" (0.6 cm)

## MATERIALS

<b>Body</b>	Polypropylene
<b>Latch</b>	ABS
<b>O-Ring</b>	Polymer
<b>Pins</b>	Stainless Steel

<b>Foam</b>	1.3 lb Polyurethane
<b>Purge Body</b>	ABS
<b>Purge Vent</b>	3 Micron Hydrophobic Non-Woven

## COLORS

 Black	 Desert Tan
-----------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------

## WEIGHT

<b>Weight With Foam</b>	8.37 lbs (3.8 kg)
<b>Weight Empty</b>	7.23 lbs (3.3 kg)
<b>Buoyancy</b>	45.15 lbs (20.5 kg)
<b>Master Pack Weight</b>	23.00 lbs (10.4 kg)

## TEMPERATURE

<b>Minimum Temperature</b>	-40°F (-40 °C)
<b>Maximum Temperature</b>	190°F (87.8 °C)

## CERTIFICATIONS

**IP67**  
**Def Stan 81-41**

## OTHER

<b>Master Pack</b>	2
<b>Nameplate</b>	yes

## ACCESSORIES



**1472**  
Shoulder Strap



**1481**  
3 pc. Replacement Foam Set



**1483**  
Replacement O-ring



**1507**  
Quick Mounts - set of 4



**1506TSA**  
TSA Lock



**1500D**  
Desiccant Silica Gel

### Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

