



# 1630

## Protector

Transport Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- **4 strong polyurethane wheels with stainless steel bearings (wheel diameter is 5.3cm)**
- **Watertight, crushproof, and dustproof**
- 3 level Pick N Pluck™ with convoluted lid foam
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Easy open double-throw latches
- Fold down handles
- Lifetime Guarantee of Excellence
- Note: Please consult a sales specialist for more details.
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Reinforced corners
- Retractable extension trolley handle
- Stackable
- Stainless steel padlock protectors



## CONFIGURATIONS



**1630**  
Standard



**1634**  
With Padded Dividers



**1630NF**  
No Foam



**1630WF**  
With Foam

## DIMENSIONS

|                              |  |
|------------------------------|--|
| <b>Interior (L×W×D)</b>      | 27.70 x 20.98" x 15.50 (70.4 x 53.3 x 39.4 cm) |
| <b>Exterior (L×W×D)</b>      | 31.28 x 24.21" x 17.48 (79.5 x 61.5 x 44.4 cm) |
| <b>Lid Depth</b>             | 3.25" (8.3 cm)                                 |
| <b>Bottom Depth</b>          | 12.14" (30.8 cm)                               |
| <b>Total Depth</b>           | 15.39" (39.1 cm)                               |
| <b>Int Volume</b>            | 5.21 ft³ (0.148 m³)                            |
| <b>Padlock Hole Diameter</b> | 0.31" (0.8 cm)                                 |

## MATERIALS

|             |               |
|-------------|---------------|
| <b>Body</b> | Polypropylene |
|-------------|---------------|

|                   |                                |
|-------------------|--------------------------------|
| <b>Latch</b>      | ABS                            |
| <b>O-Ring</b>     | Polymer                        |
| <b>Pins</b>       | Stainless Steel                |
| <b>Foam</b>       | 1.3 lb Polyurethane            |
| <b>Purge Body</b> | ABS                            |
| <b>Purge Vent</b> | 3 Micron Hydrophobic Non-Woven |

## COLORS

|   |  |
|---|--|
|  Black |  Desert Tan |
|---|--|

## WEIGHT

|                           |                       |
|---------------------------|-----------------------|
| <b>Weight With Foam</b>   | 36.00 lbs (16.3 kg)   |
| <b>Weight Empty</b>       | 31.00 lbs (14.1 kg)   |
| <b>Buoyancy</b>           | 350.00 lbs (158.8 kg) |
| <b>Master Pack Weight</b> | 42.00 lbs (19.1 kg)   |

## TEMPERATURE

|                            |                 |
|----------------------------|-----------------|
| <b>Minimum Temperature</b> | -40°F (-40 °C)  |
| <b>Maximum Temperature</b> | 190°F (87.8 °C) |

## CERTIFICATIONS

|                       |
|-----------------------|
| <b>IP67</b>           |
| <b>Def Stan 81-41</b> |

## OTHER

|                          |     |
|--------------------------|-----|
| <b>Wheels</b>            | 4   |
| <b>Extendable Handle</b> | yes |
| <b>Master Pack</b>       | 1   |
| <b>Nameplate</b>         | yes |
| <b>Reduced Area</b>      | yes |

## ACCESSORIES



**1631**  
5 pc. Replacement Foam Set



**1632**  
Pick N Pluck™ Sections Only  
(set of 3)



**1633**  
Replacement O-ring



**1635**  
Padded Divider Set



**1639**  
Lid Organizer



**1630DC**  
Document Container  
Accessory



**1507**  
Quick Mounts - set of 4



**1506TSA**  
TSA Lock



**1500D**  
Desiccant Silica Gel



**1500CI**  
Corrosion Intercept Kit

---

**Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 08-06-25*