

1730 Protector

Transport Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican[™] Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- Watertight, crushproof, and dustproof
- 5-piece foam set
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Easy open double-throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Optional Humidity gauge changes color above 40%
- Optional Manual Pressure Equalization Valve
- Stainless steel hardware and padlock protectors



CONFIGURATIONS



1730 Standard



1730NF No Foam



1730WF With Foam

DIMENSIONS

Interior (L×W×D)	34.00 x 24.00" x 12.50 (86.4 x 61 x 31.8 cm)
Exterior (L×W×D)	37.50 x 27.13" x 14.37 (95.3 x 68.9 x 36.5 cm)
Lid Depth	2.50" (6.4 cm)
Bottom Depth	10.00" (25.4 cm)
Total Depth	12.5" (31.8 cm)
Int Volume	5.9 ft³ (0.167 m³)
Padlock Hole Diameter	0.31" (0.8 cm)

MATERIALS

Body	Polypropylene	
Latch	ABS	
O-Ring	Polymer	
Pins	Stainless Steel	

Foam	1.3 lb Polyurethane	
Purge Body	ABS	
Purge Vent	3 Micron Hydrophobic Non-Woven	

COLORS

Black	Desert Tan	OD Green

WEIGHT

Weight With Foam	38.00 lbs (17.2 kg)	
Weight Empty	30.00 lbs (13.6 kg)	
Buoyancy	416.00 lbs (188.7 kg)	
Master Pack Weight	43.00 lbs (19.5 kg)	

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)	
Maximum Temperature	190°F (87.8 °C)	

CERTIFICATIONS

IP67

OTHER

Wheels	2	
Master Pack	1	
Nameplate	yes	

ACCESSORIES



Pelican 23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 sales@pelican.com • www.pelican.com

Document created on 08-23-25