

1150

Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

· Watertight, crushproof, and dustproof

- Automatic pressure equalization valve balances interior pressure, keeps water out
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Pick N Pluck[™] with convoluted lid foam
- Stainless steel hardware



CONFIGURATIONS



1150 Standard



1150NF No Foam



1150WF With Foam

DIMENSIONS

Interior (L×W×D) 8.29 x 5.79" x 3.75 (21.1 x 14.7 x 9.5 cm) Exterior (L×W×D) 9.44 x 7.80" x 4.29 (24 x 19.8 x 10.9 cm)

 Lid Depth
 0.75" (1.9 cm)

 Bottom Depth
 2.87" (7.3 cm)

 Total Depth
 3.62" (9.2 cm)

 Int Volume
 0.1 ft³ (0.003 m³)

 Padlock Hole Diameter
 0.19" (0.5 cm)

MATERIALS

Body Polypropylene
Latch Polypropylene
O-Ring Polymer
Pins Stainless Steel
Foam 1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

COLORS



WEIGHT

 Weight With Foam
 1.75 lbs (0.8 kg)

 Weight Empty
 1.61 lbs (0.7 kg)

 Buoyancy
 8.00 lbs (3.6 kg)

 Master Pack Weight
 13.95 lbs (6.3 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 210°F (98.9 °C)

CERTIFICATIONS


IP67

Def Stan 81-41

OTHER

Master Pack6Militaryyes

ACCESSORIES



Orange