



1465

Air

Pelican™ Air cases are the first in a series of remarkable innovations engineered by Pelican, the pioneers of protective cases. For over 45 years Pelican has designed and crafted the most influential protective cases in the world, and we're just getting started. With the launch of the Pelican™ Air line of cases, we're redefining the future of protection with a remarkable union of light and tough.

- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Fold down over-molded handle
- Stainless steel padlock protectors
- Press and Pull™ Latches
- Limited Lifetime Warranty
- Super-light proprietary HPX²™ Polymer - up to 40% lighter
- Waterproof O-ring seal
- User-customizable Pick N Pluck™ foam
- Waterproof, crushproof, dustproof
- Made in the USA



CONFIGURATIONS



1465
Standard



1465WF
With Foam



1465NF
No Foam

DIMENSIONS

Interior (L×W×D)	18.62 x 9.99" x 10.93 (47.3 x 25.4 x 27.8 cm)
Exterior (L×W×D)	20.83 x 12.62" x 12.75 (52.9 x 32.1 x 32.4 cm)
Lid Depth	4.94" (12.5 cm)
Bottom Depth	5.99" (15.2 cm)
Total Depth	10.93" (27.8 cm)
Int Volume	1.18 ft³ (0.033 m³)
Padlock Hole Diameter	0.31" (0.8 cm)

MATERIALS

Body	Proprietary Polypropylene Blend
Latch	ABS
O-Ring	EPDM
Pins	Stainless Steel
Foam	Polyurethane
Purge Body	ABS
Purge Vent	Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven

COLOURS

Black

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

sales@pelican.com • www.pelican.com

WEIGHT

Document created on 05-20-24

Weight With Foam	8.78 lbs (4 kg)
Weight Empty	7.12 lbs (3.2 kg)
Buoyancy	82.00 lbs (37.2 kg)

TEMPERATURE

Minimum Temperature	-60°F (-51.1 °C)
Maximum Temperature	160°F (71.1 °C)

ACCESSORIES