



# 1610M

## Protector

### Mobility Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- **4" diameter x 1.5" wide (10.2 x 3.8cm) heavy duty polyurethane wheels with stainless steel bearings**
- **Water resistant, crushproof, and dust resistant**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Easy open double-throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors



## CONFIGURATIONS



**1610M**  
Standard



**1610MNF**  
No Foam



**1610MWF**  
With Foam

## DIMENSIONS

<b>Interior (L×W×D)</b>	21.78 x 16.69" x 10.62 (55.3 x 42.4 x 27 cm)
<b>Exterior (L×W×D)</b>	26.20 x 23.00" x 13.68 (66.5 x 58.4 x 34.7 cm)
<b>Lid Depth</b>	2.05" (5.2 cm)
<b>Bottom Depth</b>	8.57" (21.8 cm)
<b>Total Depth</b>	10.62" (27 cm)
<b>Int Volume</b>	2.23 ft <sup>3</sup> (0.063 m <sup>3</sup> )
<b>Padlock Hole Diameter</b>	5/16" (12.7 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLOURS

 Black
---

WEIGHT

Weight With Foam	29.10 lbs (13.2 kg)
Weight Empty	26.30 lbs (11.9 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	210°F (98.9 °C)

CERTIFICATIONS

IP57
------

OTHER

Wheels	2
Extendable Handle	yes
Master Pack	1
Nameplate	yes
Military	yes

ACCESSORIES

				
<b>1609</b> Lid Organizer	<b>1611</b> 5 pc. Replacement Foam Set	<b>1612</b> Pick N Pluck™ Sections Only (set of 3)	<b>1615</b> Padded Divider Set	<b>1623</b> Replacement O-ring
				
<b>1507</b> Quick Mounts - set of 4	<b>1506TSA</b> TSA Lock	<b>1500D</b> Desiccant Silica Gel	<b>1610MP</b> EZ-Click™ MOLLE Panel	

---

**Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 05-17-24*