



## 2315

The hazard horizon is bright. With Class I, II, III - Division 1 and IECEx ia Safety Certification, 115 lumens and 75 meters of spot beam distance, the Pelican™ 2315 flashlight stretches light across dark, hazardous environments without being a source of ignition.

Engineered with an aluminum core and ABS overmolded plastic, these flashlights are built for rough handling and can survive hard drops. Plus, the sturdy clip attaches to a work vest for fast access and the tail switch activates raw LED power, even when using heavy-duty work gloves.

**Pelican™ 2315 - SEE THE LIGHT AT THE END OF THE TUNNEL**

- Built Pelican tough
- 2 AA Batteries (included)
- Integrated Clip
- Full / Momentary Activation Tail Switch
- Class I, II, III - Division 1 / IECEx ia Safety Certified
- IPX8 1m waterproof
- Helmet mount (included)



### DIMENSIONS

<b>Length</b>	6.22" (15.8 cm)
---------------	-----------------

### MATERIALS

<b>Body</b>	ABS
<b>O-Ring</b>	NBR
<b>Lens</b>	PC
<b>Shroud</b>	ABS
<b>Clip</b>	ABS

### COLOURS

	High Visibility Yellow
-------------------------------------------------------------------------------------	------------------------

### LIGHT SPECS

<b>Lamp Type</b>	LED
------------------	-----

### POWER

<b>Battery Size</b>	AA
<b>Battery Type</b>	Alkaline
<b>Battery Quantity</b>	2
<b>Batteries Included</b>	yes
<b>Volts</b>	3.0v

### WEIGHT

<b>Weight With Batteries</b>	4.6 oz (130 gr)
<b>Weight Without Batteries</b>	2.8 oz (79 gr)

SWITCH

Switch Type	Momentary Push Button
Light Modes	High

CERTIFICATIONS

Class I, Division 1
Class II, Division 1
Class III, Division 1
IECEX ia

FL1 STANDARD	HIGH
	115 LUMENS
	6h 0mins
	75m
	1403cd
	IPX8 (1m)