

2785

Headlamp

At long last, a high performance / long run time safety certified headlamp! The Class I, Division 1 / IECEx certified 2785 provides a Main, Downcast, Flashing, and combination LED modes. The focused Main LED provides a great distance beam while the Downcast LED projects a dispersed beam set at a 45° downward angle. This "Downcast" beam offers a number of benefits including safer illuminated pathways, reading capability, as well as convenient face to face applications. Options are plentiful as each mode is provided in an easy to select high, medium or low setting. The rear mounted battery pack is equipped with a full time battery level indicator in addition to a rear facing red LED for added safety. With over 200 lumens of high intensity light output available, coupled with the ability to last up to 100 hours in the low setting, the 2785 will support virtually all your hands free lighting needs. All this in a product that carries intrinsically safe certifications.



- Pivoting Head For Directional Beam (60°)
- Rear Mounted Red LED
- Dual Beams including Downcast LED Technology
- 3 Light Levels
- Full Time Battery Level Indication
- · Cloth and Rubber Straps Included



DIMENSIONS

Length 3.00" (7.6 cm)

MATERIALS

Body Polycarbonate (PC)

O-Ring Gasket

LensPolycarbonate (PC)ShroudPolycarbonate (PC)

COLOURS

Black High Visibility Yellow

LIGHT SPECS

Lamp TypeLEDLamp Secondary TypeLED

POWER

Battery SizeAABattery TypeAlkalineBattery Quantity4Batteries IncludedyesBattery Level Indicator3 Blue LEDs

Volts 6.0v

WEIGHT Pelican

Torrance CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 Weight With Batteries

 $\underline{sales@pelican.com} \bullet \underline{www.pelican.com}$

Weight Without 6.6 oz (187 gr) **Batteries**

Document created on 05-16-24

SWITCH

Switch Type Rotary / Push Button

Light Modes High / Medium / Low / Downcast / Spot / Flashing

CERTIFICATIONS

Class I, Division 1 IECEx ia

FL1 STANDARD	MAIN HIGH	MAIN MED	MAIN LOW
31/4	215 LUMENS	106 LUMENS	22 LUMENS
	5h 0mins	13h 0mins	98h 0mins
	108m	76m	34m
	2911cd	1445cd	290cd
The	IP54		

ACCESSORIES