



3335R

The Pelican™ 3335R is a small & light rechargeable intrinsically safe work light. The compact design fits comfortably in your hand and has the power to get you through the worst conditions, safely. The 3335R boasts performance built in providing up to 246 lumens or 58 hours of continuous run time. 3 modes are provided, High / Low / Flashing. There is a full-time battery level indicator built into the power switch, so you'll always know when it's time to recharge. The Right-Angle Adapter accessory (#3317, sold separately) transforms the flashlight into a wearable work light that allows the head to articulate, directing the light exactly where you need it.

- Full Time Battery Level Indication
- 3 modes High / Strobe / Low
- Lanyard (included)
- IP67 Rating
- Up to 246 Lumens
- Right-Angle Accessory (#3317, sold separately) transforms the 3335R into hands free wearable flashlight with head rotation capability
- Up to 58 hours run time
- Safety Certified Class I, Division 1 / IECEx ia/InMetro
- Lithium-Ion rechargeable battery included



DIMENSIONS

Length	6.11" (15.5 cm)
---------------	-----------------

MATERIALS

Body	Anti-static Impact Modified PC/PBT
O-Ring	EPDM
Lens	Anti-static coated Polycarbonate (PC)
Shroud	Anti-static Impact Modified PC/PBT

COLOURS

	High Visibility Yellow
---	------------------------

LIGHT SPECS

Lamp Type	LED
------------------	-----

POWER


Battery Size	18650
Battery Type	Lithium-Ion
Battery Quantity	1
Batteries Included	yes
Rechargeable	yes
Charge Time	12 hrs
Battery Level Indicator	RGB LED
Volts	3.7v

WEIGHT

Weight With Batteries	4.6 oz (130 gr)
Weight Without Batteries	3.0 oz (85 gr)

SWITCH

Switch Type	Push Button
Light Modes	High / Low / Flashing

FL1 STANDARD	HIGH	LOW
	246 LUMENS	30 LUMENS
	6h 15mins	58h 0mins
	151m	51m
	5718cd	649cd
	IP67	

ACCESSORIES



3317
Right Angle Adapter

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 05-16-24