



# 1506

## Air

Pelican understands that finding the right protection, with the perfect fit for your gear, is a priority. Pelican™ Air began with long protection and quickly grew to offer you deep protection. The time has come to combine those two in order to create Pelican's new Long/Deep Series. Gone are the days of dangerously forcing your equipment into the wrong size case or leaving it unprotected with no other options. With Pelican's Long/Deep series, we've created the missing link so that no matter the demands of your gear, Pelican has you covered.

- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Fold down over-molded handle
- Stainless steel padlock protectors
- Super-light proprietary HPX Polymer makes this case up to 40% lighter than the competition
- Limited Lifetime Warranty
- Super-light proprietary HPX<sup>2</sup>™ Polymer - up to 40% lighter
- Waterproof O-ring seal
- User-customizable Pick N Pluck™ foam
- Waterproof, crushproof, dustproof
- IP67 & MIL-SPEC certified
- Made in the USA



## CONFIGURATIONS



**1506**  
Standard



**1506WF**  
With Foam



**1506NF**  
No Foam



**1506TP**  
With TrekPak Divider System

## DIMENSIONS

|                              |   |
|------------------------------|---|
| <b>Interior (L×W×D)</b>      | 18.70 x 9.40" x 7.80 (47.5 x 23.9 x 19.8 cm)  |
| <b>Exterior (L×W×D)</b>      | 20.12 x 12.02" x 8.56 (51.1 x 30.5 x 21.7 cm) |
| <b>Lid Depth</b>             | 2.00" (5.1 cm)                                |
| <b>Bottom Depth</b>          | 5.80" (14.7 cm)                               |
| <b>Total Depth</b>           | 7.8" (19.8 cm)                                |
| <b>Int Volume</b>            | 0.79 ft <sup>3</sup> (0.022 m <sup>3</sup> )  |
| <b>Padlock Hole Diameter</b> | 0.31" (0.8 cm)                                |

## MATERIALS

|                   |                                 |
|-------------------|---------------------------------|
| <b>Body</b>       | Proprietary Polypropylene Blend |
| <b>Latch</b>      | ABS                             |
| <b>O-Ring</b>     | EPDM                            |
| <b>Purge Body</b> | ABS                             |

**Purge Vent**

Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven

---

**COLORS** Black

---

**WEIGHT**


|                         |                     |
|-------------------------|---------------------|
| <b>Weight With Foam</b> | 6.30 lbs (2.9 kg)   |
| <b>Weight Empty</b>     | 5.35 lbs (2.4 kg)   |
| <b>Buoyancy</b>         | 51.69 lbs (23.4 kg) |

---

**TEMPERATURE**

|                            |                  |
|----------------------------|------------------|
| <b>Minimum Temperature</b> | -60°F (-51.1 °C) |
| <b>Maximum Temperature</b> | 160°F (71.1 °C)  |

---

**ACCESSORIES**

**1506AirFS**  
4 pc. Replacement Foam Set



**1500CI**  
Corrosion Intercept Kit

---

**Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 05-11-24*