



## 1560M

### Protector

#### Mobility Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **4" diameter x 1.5" wide (10.2 x 3.8cm) heavy duty polyurethane wheels with stainless steel bearings**
- **Water resistant, crushproof, and dust resistant**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded top and side handles
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors



## CONFIGURATIONS



**1560M**  
Standard



**1560MNF**  
No Foam



**1560MWF**  
With Foam

## DIMENSIONS

|                              |  |
|------------------------------|--|
| <b>Interior (LxWxD)</b>      | 19.92 x 14.98" x 9.00 (50.6 x 38 x 22.9 cm)    |
| <b>Exterior (LxWxD)</b>      | 23.78 x 18.33" x 12.08 (60.4 x 46.6 x 30.7 cm) |
| <b>Lid Depth</b>             | 2.00" (5.1 cm)                                 |
| <b>Bottom Depth</b>          | 7.00" (17.8 cm)                                |
| <b>Total Depth</b>           | 9" (22.9 cm)                                   |
| <b>Int Volume</b>            | 1.55 ft³ (0.044 m³)                            |
| <b>Padlock Hole Diameter</b> | 5/16" (12.7 cm)                                |

MATERIALS

|            |                                |
|------------|--------------------------------|
| Body       | Polypropylene                  |
| Latch      | ABS                            |
| O-Ring     | Polymer                        |
| Pins       | Stainless Steel                |
| Foam       | 1.3 lb Polyurethane            |
| Purge Body | ABS                            |
| Purge Vent | 3 Micron Hydrophobic Non-Woven |

COLORS

|   |
|---|
|  Black |
|---|

WEIGHT

|                  |                    |
|------------------|--------------------|
| Weight With Foam | 24.30 lbs (11 kg)  |
| Weight Empty     | 21.30 lbs (9.7 kg) |

TEMPERATURE

|                     |                 |
|---------------------|-----------------|
| Minimum Temperature | -40°F (-40 °C)  |
| Maximum Temperature | 210°F (98.9 °C) |

CERTIFICATIONS

|      |
|------|
| IP57 |
|------|

OTHER

|                   |     |
|-------------------|-----|
| Wheels            | 2   |
| Extendable Handle | yes |
| Master Pack       | 1   |
| Nameplate         | yes |
| Military          | yes |

ACCESSORIES



**0343**  
Replacement O-ring



**1561**  
4 pc. Replacement Foam Set



**1562**  
Pick N Pluck™ Sections Only  
(set of 2)



**1565**  
Padded Divider Set



**1569**  
Lid Organizer



**1507**  
Quick Mounts - set of 4



**1506TSA**  
TSA Lock



**1500D**  
Desiccant Silica Gel



**1500CI**  
Corrosion Intercept Kit



**1560TPKIT**  
TrekPak Case Divider Kit



**1560TPDIV**

Extra TrekPak Dividers

---

**Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 05-09-24*