



1600EMS

Protector

EMS Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **1600 Case customized for EMS personnel**
- **CONTENTS NOT INCLUDED**
- **Watertight, crushproof, and dustproof**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Lid organizer clear cover with VELCRO® brand fasteners - keep supplies in place during transport
- Lifetime Guarantee of Excellence
- Multi layer lid organizer with numerous clean pockets - find everything right away
- Padded dividers with adjustable walls for customizing compartments to any size.
- Stainless steel padlock protectors



DIMENSIONS

Interior (LxWxD)	21.51 x 16.54" x 7.99 (54.6 x 42 x 20.3 cm)
Exterior (LxWxD)	24.39 x 19.36" x 8.79 (62 x 49.2 x 22.3 cm)
Lid Depth	1.75" (4.4 cm)
Bottom Depth	6.12" (15.5 cm)
Total Depth	7.87" (20 cm)
Int Volume	1.65 ft³ (0.047 m³)
Padlock Hole Diameter	5/16" (12.7 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLORS

 Black	 Orange
---	--

WEIGHT

Weight With Foam	18.00 lbs (8.2 kg)
Buoyancy	74.96 lbs (34 kg)
Master Pack Weight	18.50 lbs (8.4 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	210°F (98.9 °C)

CERTIFICATIONS

IP67
MIL C-4150J
Def Stan 81-41
ATA 300

OTHER

Master Pack	1
Nameplate	yes

ACCESSORIES



1605EMS
EMS Accessory Set (Lid Organizer
and Divider Set)



1506TSA
TSA Lock



1500D
Desiccant Silica Gel



1500CI
Corrosion Intercept Kit

Pelican
23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 04-29-24