

# 9490

Remote Area Lighting Systems from Pelican are the complete lighting solution for first responders, industrial and aerospace applications.

- Built Pelican tough
- Full time battery level indication with low level flashing indicator
  Deployable mast with 340 degree rotation
- Multiple deployment positions
- Convenient shoulder strap
- Quick release / Hot swappable battery design with 12 volt power supply
  Up to 6,000 lumens (calculated)
- Up to 24 hrs of run time
- Intelligent Control (allows for various light output levels)



#### DIMENSIONS

Head (L×W×D)	8.25 x 5.75" x 2.25 (21 x 14.6 x 5.7 cm)
Closed (L×W×D)	20.00 x 6.50" x 11.25 (50.8 x 16.5 x 28.6 cm)
Light Head Height (max)	72.00" (182.9 cm)

### MATERIALS

Body Head	Polypropylene Aluminum
Mast	Aluminum
Lens	Polycarbonate (PC)

## COLORS

Black

Yellow

## LIGHT SPECS

Lumens (High)	6000
Lamp Heads	1
Lamp Type	LED
Number of LEDs	10
Beam Spread	125°
IP Rating	54

#### POWER

Run Time (High)	3.50 hrs
Run Time (Med)	12.00 hrs
Run Time (Low)	24.00 hrs
Battery Type	Sealed Lead Acid (SLA)
Rechargeable	yes
Battery Lifespan	500 cycles

Charge Time	8 hrs	
<b>Battery Level Indicator</b>	Full-time battery level display and low battery warning (visible flashing)	
Sockets (Primary)	1	
Volts	12.0v	

### WEIGHT

Weight

32.00 lbs (14.5 kg)

## SWITCH

Switch Type	Silicone Rubber Keypad
Light Modes	High / Medium / Low / Flashing

## ACCESSORIES





9487 Padded Shoulder Strap **9489** Powerpack



9447 DC Vehicle Charger Cord

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 sales@pelican.com • www.pelican.com

Document created on 05-02-24