

1606

Air

Pelican understands that finding the right protection, with the perfect fit for your gear, is a priority. Pelican™ Air began with long protection and quickly grew to offer you deep protection. The time has come to combine those two in order to create Pelican's new Long/Deep Series. Gone are the days of dangerously forcing your equipment into the wrong size case or leaving it unprotected with no other options. With Pelican's Long/Deep series, we've created the missing link so that no matter the demands of your gear, Pelican has you covered.

- Automatic pressure equalization valve balances interior pressure, keeps water out
- Fold down over-molded handle
- Retractable extension trolley handle
- Stainless steel padlock protectors
- Business card holder
- Quiet rolling stainless-steel bearing wheels
- Press and Pull™ Latches
- Limited Lifetime Warranty
- Super-light proprietary HPX^{2™} Polymer up to 40% lighter
- Waterproof O-ring seal
- User-customizable Pick N Pluck[™] foam
- Waterproof, crushproof, dustproof
- IP67 & MIL-SPEC certified
- · Made in the USA



DIMENSIONS

 Interior (L×W×D)
 24.54 x 12.30" x 10.22 (62.3 x 31.2 x 26 cm)

 Exterior (L×W×D)
 27.42 x 15.13" x 11.83 (69.6 x 38.4 x 30 cm)

 Lid Depth
 2.00" (5.1 cm)

 Bottom Depth
 8.22" (20.9 cm)

 Total Depth
 10.22" (26 cm)

 Int Volume
 1.79 ft³ (0.051 m³)

 Padlock Hole Diameter
 0.31" (0.8 cm)

MATERIALS

Body Proprietary Polypropylene Blend

Latch ABS
O-Ring EPDM
Purge Body ABS

Purge Vent Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven

COLORS



WEIGHT

 Weight With Foam
 14.67 lbs (6.7 kg)

 Weight Empty
 12.45 lbs (5.6 kg)

 Buoyancy
 123.70 lbs (56.1 kg)

TEMPERATURE

 $\begin{array}{ll} \mbox{Minimum Temperature} & -60\,^{\circ}\mbox{F} \; (-51.1\,^{\circ}\mbox{C}) \\ \mbox{Maximum Temperature} & 160\,^{\circ}\mbox{F} \; (71.1\,^{\circ}\mbox{C}) \\ \end{array}$

ACCESSORIES



PL2 Padlock (2 pack)

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 sales@pelican.com • www.pelican.com

Document created on 05-03-24