

1170

Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- The hand-held electronics protection solution
- Watertight, crushproof, and dustproof
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Pick N Pluck™ with convoluted lid foam
- Stainless steel hardware



DIMENSIONS

Interior (L×W×D) 10.54 x 6.04" x 3.16 (26.8 x 15.3 x 8 cm) Exterior (L×W×D) 11.64 x 8.34" x 3.78 (29.6 x 21.2 x 9.6 cm)

 Lid Depth
 1.08" (2.7 cm)

 Bottom Depth
 2.08" (5.3 cm)

 Total Depth
 3.16" (8 cm)

 Int Volume
 0.12 ft³ (0.003 m³)

 Padlock Hole Diameter
 0.19" (0.5 cm)

MATERIALS

Body Polypropylene

LatchABSO-RingPolymerPinsStainless SteelFoamPolyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

COLORS

■ Black Desert Tan Orange OD Green
Silver Yellow

WEIGHT

 Weight With Foam
 2.10 lbs (1 kg)

 Weight Empty
 1.96 lbs (0.9 kg)

 Buoyancy
 7.25 lbs (3.3 kg)

 Master Pack Weight
 12.79 lbs (5.8 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 210°F (98.9 °C)

CERTIFICATIONS

IP67


OTHER

Master Pack

6

ACCESSORIES







1173 Replacement O-ring



1507 Quick Mounts - set of 4



1506TSA TSA Lock



1500D Desiccant Silica Gel

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 <u>sales@pelican.com</u> • <u>www.pelican.com</u>

Document created on 05-14-24