



1430 Protector

Top Loader Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **Unique top loading design**
- 3 level Pick N Pluck™ with convoluted lid foam
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Stainless steel hardware and padlock protectors
- Optional shoulder strap available



DIMENSIONS

Interior (L×W×D)	13.56 x 5.76" x 11.70 (34.4 x 14.6 x 29.7 cm)
Exterior (L×W×D)	16.40 x 8.71" x 13.15 (41.7 x 22.1 x 33.4 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	9.70" (24.6 cm)
Total Depth	11.7" (29.7 cm)
Int Volume	0.53 ft³ (0.015 m³)
Padlock Hole Diameter	0.31" (0.8 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLORS

■ Black

WEIGHT

Weight With Foam	6.50 lbs (2.9 kg)
Weight Empty	5.60 lbs (2.5 kg)
Buoyancy	59.00 lbs (26.8 kg)
Master Pack Weight	8.09 lbs (3.7 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	210°F (98.9 °C)

CERTIFICATIONS

IP67	
Def Stan 81-41	

OTHER

Master Pack	1
Nameplate	yes
Military	yes

ACCESSORIES

				
1431 5 pc. Replacement Foam Set	1432 Strap Kit	1433 Replacement O-ring	1435 Padded Divider Set	1436 Office Divider Kit
				
1438 Boat Bracket Kit	1439 Lid Organizer	1430PF Special Application Panel Frame	PL2 Padlock (2 pack)	1506TSA TSA Lock
				
1500D Desiccant Silica Gel				