

1780HL

Protector

Rifle Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican $^{\text{\tiny TM}}$ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- Fits M4, M16 firearms
- Watertight, crushproof, and dustproof
- Detachable halves serve as mobile firearm racks
- Fast loading, lockable metal cross bar
- Humidity gauge changes color above 40%
- Lifetime Guarantee of Excellence
- Manual Pressure Equalization Valve
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Rigid polyethylene tray option for 12 firearms
- Made in the USA
- \bullet 4 heavy duty polyure thane wheels with stainless steel bearings for one-man mobility



DIMENSIONS

Interior (L×W×D) 41.12 x 21.54" x 14.88 (104.4 x 54.7 x 37.8 cm) Exterior (L×W×D) 44.90 x 25.32" x 16.50 (114 x 64.3 x 41.9 cm)

 Lid Depth
 7.58" (19.3 cm)

 Bottom Depth
 7.30" (18.5 cm)

 Total Depth
 14.88" (37.8 cm)

 Int Volume
 7.63 ft³ (0.216 m³)

 Padlock Hole Diameter
 5/16" (12.7 cm)

MATERIALS

Body Polypropylene

LatchEXLO-RingPolymerPinsStainless SteelFoam1.3 lb Polyurethane

COLORS

Black

WEIGHT

 Weight With Foam
 68.40 lbs (31 kg)

 Weight Empty
 53.00 lbs (24 kg)

 Buoyancy
 500.00 lbs (226.8 kg)

 Master Pack Weight
 77.00 lbs (34.9 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 210°F (98.9 °C)

CERTIFICATIONS

Def Stan 81-41

OTHER

Wheels 4
Master Pack 1
Nameplate yes

ACCESSORIES







1782Pick N Pluck™ Sections Only (set of 4)



1783 Replacement O-ring



1506TSA TSA Lock



1500D Desiccant Silica Gel



PL2 Padlock (2 pack)

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 <u>sales@pelican.com</u> • <u>www.pelican.com</u>

Document created on 05-10-24