



9415

9410L + SAFETY = 9415

Everything that's great about the 9410L LED Lantern, plus safety certifications. At just 3 pounds and 588* lumens, the new 9415 LED Lantern packs the power without the weight. Four LEDs, powered by the latest generation Ni-MH batteries illuminate a distance of 314 yards (288* meters). And it's loaded with innovative technology and features you have come to expect from Pelican. Whether you're on a USAR team or the 3rd shift at a refinery, you'll appreciate the compact size and high output of the new 9415 LED Lantern.

Safety approved for the most volatile work areas, the 9415 LED Lantern is safe and one of the most compact, high output lanterns on the market.

9415 LED Lantern: Lightweight, big LED performance you can trust.

*Performance data is to FL 1 standards

- Built Pelican tough
- Handy push button on/off switch
- High/Low/Flashing Modes
- Super bright LED beam
- Safety Certified - Class I, Division I
- Approved to NFPA (National Fire Protection Association) 1901
- Carrying Strap included




DIMENSIONS

| | |
|---------------|-----------------|
| Length | 8.75" (22.2 cm) |
|---------------|-----------------|

MATERIALS

| | |
|---------------|--------------------|
| Body | ABS |
| O-Ring | EPDM |
| Lens | Polycarbonate (PC) |
| Shroud | EXL |

COLORS

| | |
|-------------------------------------------------------------------------------------|------------------------|
|  | High Visibility Yellow |
|-------------------------------------------------------------------------------------|------------------------|

LIGHT SPECS

| | |
|------------------|-----|
| Lamp Type | LED |
|------------------|-----|

POWER

| | |
|--------------------------------|---------|
| Battery Type | NiMH |
| Battery Quantity | 4 |
| Batteries Included | yes |
| Rechargeable | yes |
| Charge Time | 15 hrs |
| Battery Level Indicator | RGB LED |
| Volts | 4.8v |

WEIGHT

| | |
|--------------------------|-------------------|
| Weight With Batteries | 49.3 oz (1398 gr) |
| Weight Without Batteries | 0.0 oz (0 gr) |

SWITCH






| | |
|-------------|-----------------------|
| Switch Type | Push Button |
| Light Modes | High / Low / Flashing |

CERTIFICATIONS

| |
|---------------------|
| Class I, Division 1 |
|---------------------|

OTHER

| | |
|--------------|---|
| Minimum Pack | 1 |
| Package Code | B |

| FL1 STANDARD | HIGH | LOW |
|-------------------------------------------------------------------------------------|---------------|---------------|
|  | 588 LUMENS | 224 LUMENS |
|  | 4h 30mins | 11h 30mins |
|  | 288m | 176m |
|  | 20792cd | 7787cd |
|  | IPX4 | |

ACCESSORIES



9413DL
Diffuser Lens



9416
Deck/Dash Charger Base Unit



6057F
110V Transformer (USA)



6061F
Direct Wiring Rig for Fast
Charger



8056F
12v Plug-in for Fast Charger



9418
Replacement Battery

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 05-02-24