

# 9415i

#### 9410L + Safety = 9415i Everything that's great about the 9410L LED Lantern, plus safety certificates

At just 1.4kg (3 pounds) and 392 lumens, the 9415i LED Lantern packs the power without the weight. Four LEDs, powered by the latest generation Ni-MH batteries illuminate a distance of 392 meters. And it's loaded with innovative technology and features you have come to expect from Pelican.

Safety certified for the most volatile work areas, the 9415i LED Lantern is safe and one of the most compact, high output lanterns on the market.

- Built Pelican tough
- Handy push button on/off switch
- High/Low/Flashing Modes
- Super bright LED beam
- Carrying Strap included



### DIMENSIONS

Length

8.75" (22.2 cm)

#### MATERIALS

Body	Anti-static Impact Modified PC/PBT		
O-Ring	EPDM		
Lens	Anti-static coated Polycarbonate (PC)		
Shroud	Anti-static Impact Modified PC/PBT		

### COLORS

High Visibility Yellow

### LIGHT SPECS

#### POWER

Battery Size	С
Battery Type	NiMH
<b>Battery Quantity</b>	4
<b>Batteries Included</b>	yes
Rechargeable	yes
Charge Time	15 hrs
Battery Level Indicator	RGB LED
Volts	4.8v

#### WEIGHT

Weight With Batteries58.2 oz (1650 gr)Weight Without<br/>Batteries0.0 oz (0 gr)

## SWITCH

Switch Type Light Modes Push Button High / Low / Flashing

1 B

## CERTIFICATIONS

IECEx ia ATEX Zone 0 InMetro

## OTHER

Minimum Pack Package Code

FL1 STANDARD	HIGH	LOW
Mr.	392 LUMENS	144 LUMENS
	4h 30mins	11h Omins
	392m	234m
	32767cd	13747cd
	IPX4	

## ACCESSORIES



9416 Deck/Dash Charger Base Unit



6057F 110V Transformer (USA)



**6061F** Direct Wiring Rig for Fast Charger



**8056F** 12v Plug-in for Fast Charger



9418Z0 Replacement Battery

#### Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 sales@pelican.com • www.pelican.com

Document created on 06-02-24