

# 9480

Remote Area Lighting Systems from Pelican are the complete lighting solution for first responders, industrial and aerospace applications.

- Built Pelican tough
- 3 pre-set light output levels
- Up to 4,000 lumens (calculated)
- Up to 28 hrs of run time
- Full time battery level indication with low level flashing indicator
- Deployable mast with 340 degree rotation
- Multiple deployment positions
- Convenient shoulder strap
- Quick release / Hot swappable battery design with 12 volt power supply



#### **DIMENSIONS**

**Head (L×W×D)** 8.25 x 5.75" x 2.25 (21 x 14.6 x 5.7 cm) **Closed (L×W×D)** 15.50 x 6.50" x 10.25 (39.4 x 16.5 x 26 cm)

**Light Head Height** 

(max)

23.75" (60.3 cm)

### **MATERIALS**

Body Polypropylene
Head Aluminum
Mast Aluminum

**Lens** Polycarbonate (PC)

### **COLORS**

Black Yellow

### LIGHT SPECS

Lumens (High) 4000 Lumens (Med) 3000 1000 Lumens (Low) **Lamp Heads** 1 **Lamp Type** LED Number of LEDs 8 **Beam Spread** 125° **IP Rating** 54

# **POWER**

 Run Time (High)
 6.00 hrs

 Run Time (Med)
 8.00 hrs

 Run Time (Low)
 28.00 hrs

Battery Type Sealed Lead Acid (SLA)

RechargeableyesBattery Lifespan500 cyclesCharge Time8 hrs

**Battery Level Indicator** Full-time battery level display and low battery warning (visible flashing)

Sockets (Primary) 1 Volts 12.0v

# WEIGHT

**Weight** 27.50 lbs (12.5 kg)

# **SWITCH**

Switch Type Silicone Rubber Keypad
Light Modes High / Medium / Low / Flashing

# **ACCESSORIES**



### Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 <u>sales@pelican.com</u> • <u>www.pelican.com</u>

Document created on 06-02-24