



## V300C

### Vault

#### Equipment Case

Built for hard use, high impact and supreme weather resistance, new Vault series gun cases are the most rugged and secure in their class. Equipped with a host of premium protective features at a price more hunters and shooters can afford, as only the 42-year veteran of hard knocks could deliver.

- Four layers of protective foam
- Crushproof, dustproof, and weather-resistant
- High-impact polymer assures protection of your firearm, via road, trail or air
- Heavy duty handles are ergonomic and will stand up in even the toughest conditions
- Two push button latches offer secure closure with easy-open access
- Built to safely transport a variety of high-level equipment and gear



## CONFIGURATIONS



**V300C**  
Standard



**V300WF**  
With Foam



**V300WD**  
With Padded Dividers



**V300NF**  
No Foam

## DIMENSIONS

<b>Interior (L×W×D)</b>	16.00 x 11.00" x 6.50 (40.6 x 27.9 x 16.5 cm)
<b>Exterior (L×W×D)</b>	17.54 x 14.21" x 7.16 (44.6 x 36.1 x 18.2 cm)
<b>Lid Depth</b>	1.57" (4 cm)
<b>Bottom Depth</b>	4.93" (12.5 cm)
<b>Total Depth</b>	6.5" (16.5 cm)
<b>Int Volume</b>	0.66 ft <sup>3</sup> (0.019 m <sup>3</sup> )
<b>Padlock Hole Diameter</b>	5/16" (12.7 cm)

## MATERIALS

<b>Body</b>	Polyethylene
<b>Latch</b>	ABS
<b>O-Ring</b>	Polymer
<b>Pins</b>	Stainless Steel
<b>Foam</b>	1.12 lbs. ELE (Polyurethane)
<b>Purge Body</b>	ABS
<b>Purge Vent</b>	3 Micron Hydrophobic Non-Woven

COLORS

---

■ Black

WEIGHT

---

<b>Weight With Foam</b>	6.69 lbs (3 kg)
<b>Weight Empty</b>	5.82 lbs (2.6 kg)
<b>Master Pack Weight</b>	17.50 lbs (7.9 kg)

TEMPERATURE

---

<b>Minimum Temperature</b>	0°F (-17.8 °C)
<b>Maximum Temperature</b>	140°F (60 °C)

ACCESSORIES

---



**V300FS**  
4 pc. Replacement Foam Set



**1500CI**  
Corrosion Intercept Kit

---

**Pelican**  
23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 04-30-24*