



3325

Compact / Safety Certified / Tail Switch Design - All three are

combined in the 3325 LED flashlight

The compact and lightweight design begins with the use of only 3 AA alkaline batteries and yet produces over 162 lumens of brilliant light. Safety certified for use in most volatile work environments. The rear mounted switch make the 3325 a perfect match for any helmet mounted applications. The photoluminescent ("glow in the dark") shroud ensures you'll be able to locate your light even in the darkest of conditions. For added reliability, an IPX7 ingress protection level will protect the 3325 in the most severe weather conditions. Backed by Pelican's Lifetime Guarantee makes the 3325 a true value!

- 3 AA Batteries (Included)
- Glow-in-the-dark shroud
- Tail switch for easy one-handed operation
- Pelican Products, Inc.'s Lifetime Guarantee
- Ingress Protected IPX7
- Class I, Class II, Class III - Division 1 Safety Certified




DIMENSIONS

Length	6.06" (15.4 cm)
---------------	-----------------

MATERIALS

Body	EXL
O-Ring	EPDM
Lens	Polycarbonate (PC)
Shroud	Photo luminescent Polycarbonate (PC)

COLORS

 High Visibility Yellow
--

LIGHT SPECS

Lamp Type	LED
------------------	-----

POWER

Battery Size	AA
Battery Type	Alkaline
Battery Quantity	3
Batteries Included	yes
Volts	4.5v

WEIGHT

Weight With Batteries	6.1 oz (173 gr)
Weight Without Batteries	3.6 oz (102 gr)

SWITCH

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

Switch Type
Light Modes

Pelican
Push Button
On / Off

sales@pelican.com • www.pelican.com

Document created on 05-05-24

CERTIFICATIONS

Class I, Division 1

IECEX ia

Class II, Division 1

Class III, Division 1






OTHER

Minimum Pack

Package Code

1

C

FL1 STANDARD	HIGH
	171 LUMENS
	16h 0mins
	136m
	4558cd
	IPX7

ACCESSORIES